

# APOLLO

## Super Wash

**Protect against exposure to harmful cleaning chemicals**

**Simply load the machine, set the timer & walk away**

The Apollo Spray Wash uses it's own tank of hot water, detergent & inhibitor with the combination of a revolving basket & high pressure jets to clean parts.

**800** - 400 kg load - 800mm water drive basket turntable

Small to Medium capacity spray wash



**Maximum cleaning efficiency**

**Uses only hot water & detergent**

**Low running costs**

**Electric wash cycle timer**

**Water driven turntable**

**Mobile – wheel to the job**

**Simple function**

**Easy to clean tank with auto pump out**

**Environmentally friendly**

**How much skilled workshop time is spent hand cleaning parts each day!**

**You may well be wasting valuable resources.**

**Solvent cleaners can be damaging to both your employees health and the environment.**

**The Apollo spray wash uses only water & bio-degradable detergent providing an economical environmentally friendly alternative to the drudgery of hand cleaning**



**Excellence in design and quality.**

Easily the best value washer on the market today, combined with full after sales service.

**Don't settle for anything less!**

APOLLO SWE800 SPECIFICATIONS	
Basket Diameter	800mm
Job Weight (Maximum)	400kg
Job Height (Maximum)	470mm
Loading Lip Height	770mm
Water/Chem Tank Capacity	120 Litres
Power Requirement	20 amp - 3 Phase
Pump (275 Litre/min)	2.2kW 3Phase
Pump Pressure	250 kpa
Water Heaters (Temp)	3 x 2.4kW (80°C)
Machine Height	1120mm
Machine Width	1170mm
Machine Depth (Length)	1250mm
Machine Weight	340kg



Apollo SWE800 with mobility handle

The basket turntable is water driven from the supply to the spray bar. The basket rotates on a heavy duty stub axles using tapered roller bearings. One-piece closed loop fixed spray bar design gives maximum cleaning efficiency. The spray bar has no joints or hoses to fail. Spray bar has a flushing valve to allow simple cleaning of any spray hole blockages. Easy clean 120L chemical tank has two lids for full access. Large capacity easy clean gasket & particle strainers lift out with tank lids. Strainers have smaller holes than the spray bar to minimise blockages. A one-piece lid labyrinth seal area does not require a gasket or latch. There are no welded metal joints to rust. Gas strut assisted lid lift allows one-handed operation. A safety switch shuts off the pump when lid is lifted. Electronic wash timer optimises the cleaning cycle time & reduces power costs. Water temp is thermostat controlled at 80°C, turn on 30 min before use. Element protection thermostat cuts power to the elements when water level is low. Water level is controlled manually. Auto pump-out feature allows water to be pumped out in minutes for periodic machine tank cleaning. Heavy duty Australian made pump is located so that pump seal can be serviced without removal of motor. Pump overload protection fitted. Long life industrial two pack painted finish minimises paint flaking & rusting. Mobility handle allows the machine to be moved to service area. Small parts container for nuts & bolts, etc.



**Contact Chris Smith Ph: +61 2 6921 2011**  
**Australasian Machinery Dealer Services Pty Ltd**

Po Box 1050, Wagga Wagga NSW 2650  
 Website: [www.amds.com.au](http://www.amds.com.au) Email: [office@amds.com.au](mailto:office@amds.com.au) Fax: +61 2 6921 8986